



DEDICATED TO QUALITY

TERRAZIO COATING

Description:

PRIMO Terrazio coating is a quick drying terrace coating based on a special aliphatic Acrylic binder. Also it contains a high quantities of aggregates & Titanium dioxide that allows the film of the paint to be highly resistance to U.V and outdoor activities. The coating obtained with this terrazio coating results in a durable and aesthetically pleasing finish. It protects the terrace surface from weathering water seepage, and mechanical user.

Recommended Uses:

This coating is used to form a durable protective layer with high mechanical strength to terraces, pool pavements & wide scope of outdoor surfaces.

Advantages :

- Smooth, polished, or decorative finishes that elevate design.
Excellent abrasion resistant
- Has an excellent adhesion & good flow.
- This coating has a good color retention.

Surface Preparation :

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean in order to eliminate any contaminant that may affect the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

- Concrete / Masonry/ Asphalt : Wait until the concrete or masonry or asphalt is cured at least 30 days before painting it.

Recommended Primer : Aliphatic ready mix acrylic solution



DEDICATED TO QUALITY

TERRAZIO COATING

Warnings:

- Avoid application under 10°C
- Do not apply under direct sunlight
- Do not mix with other paints
- Wait 30 days before proceeding with the first cleaning .

Application:

This product is ready to be used only dilute with 25% Reducer A14. Mix well before use. Apply the second coat with 10% reducer A14. Allow a minimum drying time of 8 hours In order to properly cover the surface, it is recommended to use a 15 mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with water following their use. For spray application : May be diluted with a maximum of 30% Reducer A14.

Application Tools : Roll, brush, or spray.

Application data:

Film Thickness:

- Wet 80 - 100 µm per coat
- Dry 70 – 80 µm per coat

Drying Time:

- Tack free 30 min
- Recoat 8 hours.

Film Appearance: Flat Matt paint.



DEDICATED TO QUALITY

TERRAZIO COATING

Composition:

Aromatic Solvent	Extenders
Binder : Aliphatic Acrylic binder.	Dispersing and Wetting Agents
Titanium dioxide	Plasticizer

Technical data:

Specific Gravity g/cc	1.40-1.45
Viscosity mPa @ 25°C	20000-25000 S3, rpm3, angle 60 70%
Grinding Hegman Gauge	4-5

Colors : white,clear and wide range of Ral colors.

Coverage:

Spreading rate : 12-15 m² /US GAL (2coats).

Packing:

Drums of 20 liters ,USG & Quartz.

Cleaning:

Clean all the equipment with Thinner immediately after using.

Disposal:

Consult your municipality in order to dispose of paint residues according to environmental regulations. Do not pour down a drain or storm sewer.

Storage:

Store far from direct sun light at temperature between 10 – 35° C



DEDICATED TO QUALITY

TERRAZIO COATING

Shelf life:

It has shelf life 3 years in unopened container at cool and dry conditions.

HEALTH AND SAFETY:

Proper ventilation should be observed during application and drying to avoid suffocation. Wear protective clothes and masks.

Caution:

- Keep lid closed when not in use.
- Avoid freezing.
- Keep away from children's reach and avoid contact with eyes.

NOTE : The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. All PRIMO Paints products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.