



DEDICATED TO QUALITY

INTERNO FLAT WALL FINISH LOW VOC INTERIOR EMULSION 3-100

Description:

This product is water based **LOW VOC** emulsion matt based on acrylic binder that has good quality for interior use. It is easy to apply, without splashing and dries quickly. This Latex Emulsion can be used for commercial, industrial and residential projects.

Advantages:

- Provides an excellent leveling and achieve a smooth finish.
- It will retain its sheen and has good color retention.

Surface Preparation:

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean in order to eliminate any contaminant that may affect the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

Flaking or peeling paint: Using a scraper, remove the weakened and loose paint, then sand the edges of the surface to make it smooth. A repair compound should be used to fill holes and uneven surfaces.

Sand with a grade #100 sanding paper.

Recommended Primer: On a dry wall : Use PRIMO Water Based Primer Sealer white or Clear Series 3-6001 or 3-6000.

Recommended uses:

This Interno Emulsion water based paint must be applied on prepared and primed surfaces (Use PRIMO Water Based Primer Sealer white or Clear Series 3-6001 or 5-6000. It is recommended for drywall, wall putty, concrete, masonry, cement and wood. Its flat matt finish allows for easy cleaning. It will retain its sheen and it has good color retention.

Application:

This Product is ready to be used only dilute with 20% of water. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat for pale colors and 8 hours for dark colors.

In order to properly cover the surface, it is recommended to use a 15 mm lint free roller and a quality nylon-polyester brush.



DEDICATED TO QUALITY
INTERNO FLAT WALL FINISH LOW VOC INTERIOR EMULSION
3-100

For spray applications: May be diluted with a maximum of 10% water.

Film Thickness	Drying Time
Wet 60 – 70 microns per coat	Tack free 60 min
Dry 40 – 50 microns per coat	Recoat 8 hours

Chemical Composition:

Diluent : Water	Biocide
Binder : Acrylic.	Dispersing and Wetting Agents
Titanium dioxide & Extenders.	Antifoam & Coalescing agents.

Maintenance:

This paint requires 30 days drying time before proceeding with a first cleaning. Only use mild, non-abrasive cleaners and a soft cloth. Clean the surface with a light, circular motion.

Technical data:

Color	Available in all ranges Pastel, medium and deep ones See PRIMO Decorative Catalogue.
Specific gravity g/cc	1.55- 1.1.65
Viscosity mPa@25 °C, S3,rpm 3,angle 30-40 %	15000-25000
PH	8-9
Grind Hugman Gauge µm	5-6

Packing:

Drums of 17 liters &US Gallon.

Cleaning:

Clean all the equipment with water immediately after using.

Coverage:

Spreading rate : 40-45 m² / US Gallon.



DEDICATED TO QUALITY
INTERNO FLAT WALL FINISH LOW VOC INTERIOR EMULSION
3-100

Storage:

Store at temperature between 10 – 35° C

Shelf life:

Shelf life 3 years of in unopened container at cool and dry condition away from direct sunlight.

Health & Safety:

Proper ventilation should be observed during application. Wear protective clothes and masks.

Caution:

- Keep away from children's reach and avoid contact with eyes
- Keep lid closed when not in use.
- Avoid Freezing

Warnings:

- Avoid application under 10°C or above 40°C.
- Do not apply under direct sunlight.
- Do not mix with other paints.
- Do not use on flooring.
- Wait 30 days before proceeding with the first cleaning .

NOTE : The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. All PRIMO Paints products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.