



DEDICATED TO QUALITY

PRIMO ESTERNO SUPER RUBBER EMULSION INTERIOR-EXTERIOR

Description:

It is a premium quality 100% acrylic latex exterior paint designed for use on most interior-exterior surfaces, is specially formulated to provide excellent weather resistance, easy application and a quick curing time, resulting in a long lasting, uniform finish. Forming a breathable film that allows moisture vapor to pass through, it prevents the penetration of liquid water with a high resistance to blistering and peeling.

Recommended Uses:

This ESTERNO latex is specifically formulated to meet the performance requirements of residential and commercial markets. It can be applied on previously painted exterior and interior surfaces such as wood, aluminum, concrete, metal and masonry.

Available Sheens:

Matt @ 60°C	3-5%
Satin @ 60°C	12-15%
Gloss @ 60°C	40-50%

Features:

- Provides a Tough, Durable, Mildew Resistant Coating.
- Great Dirt Resistance.
- Great Adhesion.

Surface Preparation:

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean in order to eliminate any contaminant that may affect the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted. Flaking or peeling paint: Using a scraper, remove the weakened and loose paint, then sand the edges of the surface to make it smooth. A repair compound should be used to fill holes and uneven surfaces. Sand with a grade #100 sanding paper



DEDICATED TO QUALITY

ESTERNO ANTIBACTERIAL SUPER RUBBER EMULSION INTERIOR - EXTERIOR

Application:

This product is ready to be used only dilute with 20% of water. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat for pale colors and 8 hours for dark colors. In order to properly cover the surface, it is recommended to use a 15 mm lint free roller and a quality nylon-polyester brush. For spray application : May be diluted with a maximum of 10% water.

Film Thickness	Drying Time
Wet 60 – 70 microns per coat	Tack free 60 min
Dry 40 – 50 microns per coat	Recoat 8 hours

Recommended Primer: On a dry wall : Use PRIMO Water Based Primer Sealer white or Clear Series 3-6001 or 3-6000.

- Avoid application under 10°C or above 40°C .
- Do not apply under direct sunlight.
- Do not use on flooring & Do not mix with other paints.
- Wait 30 days before proceeding with the first cleaning .

Chemical Composition:

Diluent : Water	Biocide, Anti fungus
Binder : Acrylic.	Dispersing and Wetting Agents
Titanium dioxide & Extenders.	Antifoam & Coalescing agents.

Technical data:

Color	See PRIMO Decorative Catalogue.
Specific gravity g/cc	1.25- 1.40
Viscosity mPa@25 °C, S3,rpm3,angle30-40 %	10000-20000
PH	8-9
Grind Hugman Gauge µm	5-6



DEDICATED TO QUALITY

ESTERNO ANTIBACTERIAL SUPER RUBBER EMULSION INTERIOR - EXTERIOR

Coverage:

Spreading rate : 40-50 m² / US Gallon.

Packing:

Plastic Drums of 17 liters & US Gallon.

Cleaning:

Clean all the equipment with water immediately after using.

Storage:

Store far from direct sun light at temperature between 10 – 35° C

Shelf life:

Shelf life 3 years of in unopened container at cool and dry condition away from direct sunlight.

HEALTH AND SAFETY:

Proper ventilation should be observed during application and drying to avoid suffocation. Wear protective clothes and masks.

Caution:

- Keep away from children's reach and avoid contact with eyes
- Keep lid closed when not in use.
- Avoid freezing

NOTE : The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. All PRIMO Paints products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.