



DEDICATED TO QUALITY
WOOD ADHESIVE YELLOW

Description:

This PRIMO product is a light yellow, based on modified PVA, medium to fast setting adhesive which is recommended for substrates such as paper, cartoon, wood, fabric, non-wovens and foam.

Properties:

- Excellent tack & fast drying.
- Excellent adhesion on multiple substrates.
- High performance & low VOC.
- Suitable for porous & nonporous surface
- Needs no diluents.

Applications:

- Interior applications with frequent short term exposure of the bonds to running or condensed water.
- Interior applications which are exposed to high relative humidity.
- Exterior applications which are not exposed to weather factors.
- Bonding of wood, board, chipboard.
- Adhesive for paper and cartoons.
- Adhesive forms a powerful, long-lasting bond between foam & wood .
- Bonding joints in block bonding of softwood, hardwood and chipboard.

Substrates:

The surface should be flat, clean, dry free from dust and grease. Slightly sanding smooth substrate such as non-porous surfaces can improve the adhesion. We recommend a preliminary adhesion and compatibility test on every surface.

Warnings:

- Avoid application under 10°C or above 40°C.
- Do not apply under direct sunlight.
- Do not mix with other paints.



DEDICATED TO QUALITY
WOOD ADHESIVE YELLOW

Chemical Composition:

Diluent : Water	Biocide
Binder : Modified PVA	
Plasticizer	Antifoam

Technical Data:

Color	Yellow
Specific gravity g/cc	1.0
Viscosity mPa@25 °C, S3, rpm3, angle 20-25%	7000-10000
PH	6-7

Packing:

Plastic Pail of 20 liters ,US Gallon, US Quart.

Cleaning:

Clean all the equipment with water .

Shelf life:

At least 12 months in original, unopened packaging in a cool and dry storage place with temperature between +5°C and +25°C.

HEALTH AND SAFETY:

Wear gloves & masks while using this glue.

Caution:

- Keep away from children's reach and avoid contact with eyes
- Keep lid closed when not in use.
- Avoid Freezing



DEDICATED TO QUALITY
WOOD ADHESIVE YELLOW

NOTE : The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. All PRIMO Paints products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.