



DEDICATED TO QUALITY **WOOD GLUE WHITE**

Description:

Poly vinyl acetate water-based adhesive of high performances, suitable for bonding soft and hard-woods with themselves and with laminates. Wood adhesive glues are specialized adhesives designed for strong wood-to-wood bonds, with PVA (polyvinyl acetate) being the standard choice for furniture and general woodworking.

Properties:

- Easy to tool
- Transparent after drying
- High end strength
- Fast drying time
- Resistant against high temperatures

Application:

- Interior applications with frequent short term exposure of the bonds to running or condensed water.
- Interior applications which are exposed to high relative humidity.
- Exterior applications which are not exposed to weather factors.
- Bonding of wood, board, chipboard, veneer
- Assembly gluing of soft wood
- Construction bonding such as mortise and tenon joints, punches, etc.
- Bonding joints in boards and block bonding of softwood, hardwood and chipboard.

Substrates:

Most non-porous and porous substrates like timber, wood, cardboard, laminates, etc. Nature: The surface should be flat and well fitting as well as clean, dry and free of dust and grease. Surface preparation: Slightly sanding smooth substrate such as non porous surfaces can improve the adhesion.

We recommend a preliminary adhesion and compatibility test on every surface.



DEDICATED TO QUALITY
WOOD GLUE WHITE

Chemical Composition:

Diluent : Water	Biocide
Binder : PVA	
Plasticizer	Antifoam

Technical data:

Color	White orYellow
Specific gravity g/cc	1.0-1.05
ViscositymPa@25 °C, S3, rpm3, angle 20-30%	7000-15000
PH	7-8

Packing:

Drum 50 Kg. , Plastic Pail of 17 liters , US Gallon, 500 ml.

Cleaning:

Clean all the equipment with water

Shelf life:

At least 12 months in original, unopened packaging in a cool and dry storage place with temperature between +5°C and +25°C.

Warnings:

- Avoid application under 10°C or above 40°C.
- Do not apply under direct sunlight.
- Do not mix with other paints.



DEDICATED TO QUALITY
WOOD GLUE WHITE

Health & Safety:

Wear gloves & masks while using this glue.

Caution:

- Keep away from children's reach and avoid contact with eyes
- Keep lid closed when not in use.
- Avoid Freezing

NOTE : The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. All PRIMO Paints products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.