



DEDICATED TO QUALITY SPRAY PAINT

Description:

Quick dry Acrylic based spray paint for all Interior and Exterior applications. This Primo spray product has good hiding power, excellent coverage and gives protection against corrosion.

Properties:

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean in order to eliminate any contaminant that may affect the adhesion or the curing of the product.

The surfaces must be well sanded and dusted.

Concrete / Masonry : Wait until the concrete or masonry has cured at least 30 days before repainting it.

Colors Available:

Color & Code	Appearance
Sky Blue # 15	GLOSS
Scarlet red # 23	GLOSS
Mission Brown # 29	GLOSS
Black # 39	GLOSS
White # 40	GLOSS
Canary Yellow # 41	GLOSS
Cream White # 43	GLOSS
Post Green # 77	GLOSS
Royal Blue # 136	GLOSS
Lacquer # 190	GLOSS
Black # 4	MATT
White # 1007	MATT
Flash Gold # 188	METALLIC COLOR
Silver # 36	METALLIC COLOR
Chrome Gold	CHROMATE
Chrome Silver	CHROMATE



DEDICATED TO QUALITY SPRAY PAINT

Performance & Uses:

- Quick drying, smooth finish.
- Premium quality, high durable.
- Ideal for wood, metals, plastic, automotive and motorcycle, equipment etc.
- Available in 16 colors including metallic.
- Interior and exterior application.
- Non fading, none yellowing, weather resistant.
- High coverage ability without running or excessive thickness
- Aerosolform.

Application:

Shake well the spray can before use. Hold the container approximately 30 cm away from the object to be painted. Keep the can motion from side to side so that the coating is deposited evenly.

Better to apply several thin coating at an interval of 10 minutes.

Better to store can at room temperature

Packing:

Spray can of 400ml.

Shelf life:

Shelf life 3 years at normal conditions.

Storage:

Store at temperature between 10–35° C

HEALTH AND SAFETY:

Proper ventilation should be observed during application. Wear protective clothes and masks.

Caution:

- Keep away from children's reach and avoid contact with eyes
- Keep lid closed when not in use.
- Avoid Freezing



DEDICATED TO QUALITY

SPRAY PAINT

Warnings:

- Avoid application under 10°C or above 40°C.
- Do not apply under direct sunlight.
- Do not mix with other paints.
- Wait 30 days before proceeding with the first cleaning.

NOTE : The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. All PRIMO Paints products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.